



## RESTORATION WASH, GLOSS, TRACTION & BUFF

Formerly known as  
RESTORE

- New technology floor restoration compound
- Specifically formulated to clean, polish and improve slip resistance on most floors in on simple step

	ES95
APPEARANCE	Clear liquid
ODOUR	None
SOLUBILITY	Soluble
RELATIVE DENSITY	~1.03
pH-VALUE	11.4-12.4
VISCOSITY	N/A
SHELF LIFE	

SIZES	
ES95	3.78 L (1.0 U.S. gallon)

### BENEFITS

**VERSATILE:** Cleans, polishes, restores and improves slip resistance

**ECONOMICAL:** Saves money and reduces the need for stripping

**SAFE:** Compatible with most floors

**PROTECTS:** Resists dirt, stains, scuffs and scratches

### DIRECTIONS

#### Lightly Soiled Floors

1. Dust mop floor
2. Dilute 45-60 mL of #95 to 3.78 L water (1 1/2 oz. - 2 oz. of #95 per gallon of water)
3. Damp mop, for large areas use an auto scrubber
4. Let dry

#### Mop Restoration and Cleaning Applications

1. Dust mop floor
2. Dilute 90-120 mL (3-4 oz.) of #95 to 3.78 L (1 US gallon) of water
3. Using a clean mop, apply solution to the floor in the same manner as damp mopping
4. Allow to sit for 3-5 minutes, then pick up the solution
5. Allow to dry, then burnish with a natural hair burnishing pad

#### Spray Buff Restoration

1. Dust mop floor
2. Dilute 360 mL (12 oz.) of #95 to 3.78 L (1 US gallon) of water
3. Liberally apply ahead of buffer and spray buff to a high gloss

#### Auto Scrubber Restoration

1. Dilute 90-120 mL (3-4 oz.) of #95 to 3.78 L (1 US gallon) of water
2. Scrub with a red pad on a double pass procedure. Scrub only on the first pass (do not pick-up) and then on the second pass, pick-up only, do not scrub. The longer the solution sits between passes the better the results
3. Allow to dry
4. Burnish with floor machine and burnishing pad

**CAUTION:** KEEP FROM FREEZING

### DISPOSAL

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

### PERSONAL PROTECTION

Please refer to product label and SDS