



GREEN & BRITE FLOOR FINISH

- For day after day high traffic and high gloss floors
- Durable, stain and black heel mark resistant
- Zinc-Free, Free of phosphates, EDTA and bleach

	ES18
APPEARANCE	Blue Liquid
ODOUR	Mild
SOLUBILITY	Soluble
RELATIVE DENSITY	1.014
pH-VALUE	~7.5-8.5
VISCOSITY	Similar to water
SHELF LIFE	3 years

SIZES	
ES18-4	3.78 L (1 US Gal)
ES18-18	18.9 L (5 US Gal)

BENEFITS

- Zinc-free
- Low odour
- Packaging contains recycled material
- Free of phosphates, EDTA and bleach
- Does not comprise of material originating from nonylphenol (NP)



PRODUCT CERTIFIED FOR REDUCED ENVIRONMENTAL IMPACT. VIEW SPECIFIC ATTRIBUTES EVALUATED: UL.COM/EL UL 2777



Floor coating and finishing material as to slip resistance only 18RL
 Matériau de revêtement et de finition à plancher en ce qui concerne la résistance au glissement seulement 18RL

DESCRIPTION

For day after day high traffic and high gloss floors. Durable, stain and black heel mark resistance. Designed for both spray buffing and UHS burnishing systems. Easy to clean & easy to maintain.

DIRECTIONS

INITIAL APPLICATION

- Before application, remove old coatings with a Green Certified Floor Stripper
- Pick up stripper solution using a mop or wet vacuum. Thoroughly rinse floors with clean water and allow to dry.
- OPTIONAL: Apply 2 thin coats of sealer (such as ES82) to high-traffic areas, old or porous floors.
- Apply 3 to 5 coats of ES18 Green & Brite Floor Finish if sealer applied, or 4 to 6 coats if no sealer applied.
- Allow 30-45 minutes for floor to dry between each coat.

ROUTINE MAINTENANCE

- Sweep floor with a dust mop
- As needed scrub with a blue or green pad and ES91 Deep Scrub.
- Rinse and let dry, then dry mop.
- Apply 2 coats of ES18 Green & Brite Floor Finish.
- Strip floor when desired results cannot be achieved with routine maintenance.

PERSONAL PROTECTION

Please refer to product label and SDS.