



HIGH GLOSS FLOOR FINISH

- For day after day super high gloss floors
- Durable, stain and black heel mark resistant
- Designed for UHS burnishing system
- Easy to clean and maintain
- UL approved for slip resistance

ES80

	ES80
APPEARANCE	White emulsion
ODOUR	Mild acrylic
SOLUBILITY	Emulsifiable
RELATIVE DENSITY	1.04
pH-VALUE	8-9
VISCOSITY	Water thin
SHELF LIFE	

SIZES		
ES80	18.9 L (5.0 U.S. gallon)	3.75 L (1.0 U.S. gallon)

DISPOSAL

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

PERSONAL PROTECTION

Please refer to product label and SDS

DIRECTIONS

STRIP AND RECOAT

1. Before application, remove old coatings with ES85 Scrub Free Stripper or ES90 Clean Cut Concentrate Stripper
2. Pick up stripper solution using a mop or wet vacuum
3. Thoroughly rinse and neutralize floor. No sealer required
4. Apply 3 to 4 coats of ES80 High Gloss Floor Finish
5. Allow at least 15 minutes after dry to touch between coats

SCRUB AND RECOAT

1. Recoat every 4-8 weeks, or as needed
2. Dry mop area
3. Scrub with a blue or green pad and ES70 General Purpose Cleaner
4. Rinse and let dry
5. Apply 1-2 coats of ES80 High Gloss
6. Floor Finish

CLEANING RESTORING GLOSS

1. Dry mop daily
2. Burnish regularly

CLEAN AND SHINE

Automatic Scrubbers

1. Dry mop
2. Clean with ES84 Neutral Cleaner - use a red pad
3. Let dry - burnish

Mop and Bucket

1. Dry mop
2. Damp mop with ES84 Neutral Cleaner
3. No Rinse required
4. Let dry - burnish