



BARRICADE SEALER/FINISH

- An acrylic blend of polymers with excellent protective properties
- Resists the penetration of over 30 common staining and soiling agents
- Excellent durability, ideal for scrub and recoat

	ES82
APPEARANCE	White emulsion
ODOUR	Mild acrylic
SOLUBILITY	Emulsifiable
RELATIVE DENSITY	N/A
pH-VALUE	7.5-8.5
VISCOSITY	Water thin
SHELF LIFE	

SIZES		
ES82	18.9 L (5.0 U.S. gallon)	3.75 L (1.0 U.S. gallon)

BENEFITS

- Recommended for spray buffing with floor machines up to 1000 RPM
- UL approved for slip resistance

DIRECTIONS

STRIP AND RECOAT

1. Before application, remove old coatings with ES85 Scrub Free Stripper or ES90 Clean Cut Concentrated Stripper
2. Pick up stripper solution using a mop or wet vacuum
3. Thoroughly rinse and neutralize floor
4. Apply 2 to 4 coats of ES82 Barricade Sealer/Floor Finish
5. Allow at least 15 minutes after dry to touch between coats

SCRUB AND RECOAT

1. Dry mop area
2. Scrub with ES70 or ES91, then rinse
3. Apply ES82 Barricade Sealer/FloorFinish with a finish mop

BUFFING AND BURNISHING

- Ideal for buffing with floor machines up to 1000 RPM

DISPOSAL

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

PERSONAL PROTECTION

Please refer to product label and SDS