



SPRAY BUFF SOLUTION

- Enhances the gloss and removes soil and scuff marks on high traffic or damaged areas of the floor
- Actually increases the durability of the floor finish

	ES86
APPEARANCE	Opaque white liquid
ODOUR	Oca
SOLUBILITY	N/A
RELATIVE DENSITY	1.01
pH-VALUE	8-9
VISCOSITY	Water thin
SHELF LIFE	

SIZES	
ES86	3.78 L (1 U.S. gallon)

DIRECTIONS

1. Dry/Dust Mop the floor and remove any gum, tape, etc.
2. Wash/Damp Mop the floor using ES #84 Neutral Floor Cleaner at proper dilution
3. Allow to dry
4. Spray a light mist on the floor and buff with a red or tan pad for a standard machine, or a spray buff pad using a burnisher (1000 -1500 RPM)
5. Do a small area at a time until the floor is dry, clean and glossy
6. Continue to do small sections until the complete area is done. When the pad becomes dirty, flip it over or replace it with a new pad
7. Dry mop again to remove dirt crystals which have

DISPOSAL

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

PERSONAL PROTECTION

Please refer to product label and SDS

CAUTION: KEEP FROM FREEZING