



## BLOCKADE ALL ACRYLIC BASED CONCRETE SEALER

- Thermoplastic all acrylic water based sealer for use on concrete, terrazzo and other masonry floors and walls
- Recommended for warehouses, food processing plants and similar facilities



Floor coating and finishing material as to slip resistance only 18RL  
Matériau de revêtement et de finition à plancher en ce qui concerne  
la résistance au glissement seulement 18RL

### BENEFITS

- Easy application – Fast drying
- Low odor
- Excellent resistance to water blushing
- Completely recovers to visually clear film when water is removed
- High level of block resistance
- Excellent stain resistance to : Food Stains, Used Motor Oil, Water, 10% Sodium Hydroxide, 10% Calcium Chloride, 10% Sodium Chloride
- No yellowing
- UL Approved for slip resistance
- Food Grade Approved

**Note:** Not recommended for automotive garages, machine shops where brake fluid, gasoline are prevalent

### DIRECTIONS

- See label for complete instructions
- Temperature should be at least 50°F or 10°C when applying
- For best results allow 8 hours before using heavy equipment on floor
- To achieve maximum cure, allow 24 hours cure time

### DISPOSAL

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

### PERSONAL PROTECTION

Please refer to product label and SDS

	ES89
APPEARANCE	Opaque White Liquid
ODOUR	None
SOLUBILITY	Soluble
RELATIVE DENSITY	1.025
pH-VALUE	8.3
VISCOSITY	Similar to water
SHELF LIFE	3 years

SIZES	
ES89	18.9 L (5.0 U.S. gallon)