



ES95+ TRACTION/RESTORATION

- Enhances gloss
- Improves foot traction
- Superior deep clean
- Use on any type of floor

	ES95+
APPEARANCE	Clear Straw-Coloured Liquid
ODOUR	Polymer
SOLUBILITY	Soluble
RELATIVE DENSITY	1.020
pH-VALUE	~7.8
VISCOSITY	Similar to water
Shelf Life	3 years

SIZES	
ES95+-4	3.78 L (1 U.S. Gal)

BENEFITS

- EcoLogo Certified
- Certified by UL for slip resistance
- Readily biodegradable
- Packaging contains recycled material
- Free of phosphates and EDTA
- Free of phthalates and perfluorooctanoic acid (PFOA) derivatives
- Non-toxic towards aquatic life



DESCRIPTION

- Instantly improves the slip resistant properties of any surface it is applied to
- Can be applied with a mop or auto scrubber
- Use on any type of floor including resilient tile, stone, concrete, and sealed wood

DIRECTIONS

- Thoroughly sweep the floor to remove any dirt or soil
- Floors with heavy concentrations of oil, grease, or animal protein soils should initially be cleaned with a degreaser to obtain optimum results
- Dilute ES95+ Traction/Restoration 2 ounces per gallon (60mL/3.78L) with warm water
- ES95+ Traction/Restoration may be applied using either a damp mop or automatic scrubber. A two bucket system, in which one bucket holds the ES95+ Traction/Restoration solution and one into which the soiled solution is wrung, will provide the most satisfactory results. Use a clean cotton or cotton/synthetic combination mop to damp mop the floor. For use in an automatic scrubber, place the ES95+ Traction/Restoration solution in the feed tank of the automatic scrubber. The solution may be applied, scrubbed, and vacuumed in one step. Following damp mopping or scrubbing, allow the floor to dry completely, but do not rinse
- To restore gloss or repair scuffs, buff the treated area with an appropriate buffing pad or brush with either a low or high speed buffing machine

PERSONAL PROTECTION

Please refer to product label and SDS