



GREEN CERTIFIED FLOOR FINISH

- For day after day high traffic & high gloss floors
- Durable, greater initial gloss

	ES98
APPEARANCE	White opaque liquid
ODOUR	Solvent
SOLUBILITY	Dispersible
RELATIVE DENSITY	N/A
pH-VALUE	7.5-8.5
VISCOSITY	Water thin
SHELF LIFE	3 years

SIZES		
ES98	18.9 L (5.0 U.S. gallon)	3.78 L (1.0 U.S. gallon)

BENEFITS

- One of the very best Green Certified Finishes (EcoLogo/UL) on the market
- Very durable with a great gloss
- Wet look finish that can be UHS burnished, buffered or left as a scrub and recoat
- Easy to apply and maintain
- UL approved for slip resistance
- Greater durability, gloss, scuff and black mark resistance

DISPOSAL

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.



PRODUCT CERTIFIED FOR REDUCED ENVIRONMENTAL IMPACT. VIEW SPECIFIC ATTRIBUTES EVALUATED. UL.COM/EL UL 2777



Floor coating and finishing material as to slip resistance only 18RL
Matériau de revêtement et de finition à plancher en ce qui concerne la résistance au glissement seulement 18RL

DIRECTIONS

STRIP AND RECOAT

1. Before application, remove old coatings with a Green Certified stripper
2. Pick up stripper solution using wet vacuum
3. Thoroughly rinse floors with clean water after stripping or deep scrubbing, let dry, then dry mop. No sealer required except for new floors, very porous floors, or very high traffic. If so, apply 1 or 2 thin coats of Barricade ES82 Sealer/Finish
4. Apply 3 to 4 coats of ES98 Green Certified Floor Finish if sealer applied, or 5 to 6 coats if no sealer applied
5. Allow at least 15 minutes after dry to touch between coats

SCRUB AND RECOAT

1. Recoat every 4 – 8 weeks, or as needed
2. Dry mop area
3. Scrub with a blue or green pad and ES91 Deep Scrub
4. Rinse and let dry, then dry mop
5. Apply 1 –2 coats of ES98 Green Certified Floor Finish

CLEANING - RESTORING GLOSS

- Dry mop daily
- Burnish regularly. Do not use aggressive pads. Use a moderate white buffing pad or a natural fibre pad

CLEAN AND SHINE

Automatic Scrubbers

- Dry mop
- Clean with ES84 Neutral Cleaner or ES95 (description) - use a red pad

Mop & Bucket

- Dry mop
- Damp mop with ES84 Neutral Cleaner or ES95 (description) - use red pad
- Allow floor to dry - burnish

PERSONAL PROTECTION

Please refer to product label and SDS