



IMPREGNATOR SEALER – STONE, TILE & GROUT

- Water based design to protect against water and oil based stains on all grouted surfaces
- May be used on ceramic tile, terrazzo, and concrete floors
- Grout sealer
- Easy application

	ES99
APPEARANCE	Hazy White Liquid
ODOUR	None
SOLUBILITY	Soluble
RELATIVE DENSITY	1.004
pH-VALUE	7.1
VISCOSITY	Similar to water
SHELF LIFE	

SIZES		
ES99	18.9 L (5.0 U.S. gallon)	3.78 L (1.0 U.S. gallon)

DIRECTIONS

1. Clean grout/floor and allow to dry for 6 to 12 hours to ensure a thorough dry (grout should be one consistent color)
2. Apply ES99 Impregnator Sealer with a finish mop if applying to the total surface. If desiring to only seal the grout, use a moist squeegee or sprayer to direct product to the grout and wipe excess material off floor with a clean, dry microfiber mop
3. Let sit & penetrate for 2 to 6 hours
4. Apply a second coat
5. If possible, allow to dry for 24 hours before traffic
6. Maximum protection is achieved after 24 hours
7. For daily cleaning, use ES 84 Neutral Floor Cleaner

CAUTION

- Protect all adjoining surfaces and all other surfaces in which you do not want to have ES99 come in contact with and all non-masonry surfaces
- This product does not protect floors against sub floor humidity
- Keep from freezing

DISPOSAL

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

PERSONAL PROTECTION

Please refer to product label and SDS